

The list is showing all head-styles which are available in the series 141.

Silver drawing means: head with steel core.

The number shown right besides every picture is the part number used for ordering. Please replace the field „xx“ by the spring force value you'd like to have. The available spring options are listed below.

Example of a completed ordering number:

141.05.06.10

Available spring forces with values in Newton (N) and ozs. and the adding code for the part number:

Code	Preload (N) (oz.)	Rated Force (N) (oz.)
10	0.4 1.38	1.0 3.46



Further Technical Data:

Minimum center spacing:	1.27	mm	.05	inches
Extension height:	6.89	mm	.271	inches
Overall length:	34.59	mm	1.362	inches
Barrel diameter:	0.79	mm	.031	inches
Plunger shaft diameter:	0.6	mm	.024	inches
Maximum travel:	6	mm	.236	inches
Recommended (rated) travel:	4.2	mm	.165	inches
Temperature range:	-55°C ... +105°C		-67°F ... +221°F	
Typical electrical resistance:	16	mΩ		
Rated electrical current load:	2	amps		
Maximum current load:	3	amps		
Typical life-time in cycles:	1 x 10 ⁶	cycles		


Further spring forces and head styles available on request. Please allow longer delivery for special configurations.

Materials:

Plunger:	Copper Alloy, gold plated
Barrel:	Copper Alloy, gold plated
Spring:	Music Wire, gold plated



S 141.00-C
Open Crimp End



S 141.00-L
Solder Cup

For the installation of the receptacles the mounting plate requires precise drilling. In the fixture business there are some typical base materials used for the pin plates which are different in drill bit diameters and machining parameters. The table is showing the recommended drill diameter and the order numbers needed when ordering drill bits from us. For machining parameters please consult factory.

Receptacle with Press-Ring, pressed into Plate Material			
Material	Drill- \varnothing		Part No.
CEM1 (also called EP105)	.0386 in.	0.98 mm	500-0098
FR4 (G10, Hgw 2372 or Hgw 2372.1)	.0390 in.	0.99 mm	500-0099
Press-Ring or Stop Ring used as a Collar			
CEM1 (also called EP105)	.0378 in.	0.96 mm	500-0096
FR4 (G10, Hgw 2372 or Hgw 2372.1)	.0382 in.	0.97 mm	500-0097